

# Eternal 30

*Engineered Vinyl*



Floor: EVET 3002 Matt

**18 Colours / 1 Finish / 2 Sizes**

Eternal 30 is a range of highly textured vinyl planks suitable for domestic and light commercial areas. In colours from subtle oaks to burnt woods, this range is available in dryback and rigid acoustic options. The latter comprises an integrated acoustical pad contributing to a high sound reduction.



Floor: EVET 3011 Matt



Floor: EVET 3006 Matt



Floor: EVET 3012 Matt



EVET 3008



EVET 3016



EVET 3013



EVET 3009



EVET 3005



EVET 3017




EVET 3012




EVET 3003




EVET 3015




EVET 3004




EVET 3001



EVET 3014




EVET 3011



EVET 3010




EVET 3018



EVET 3006



EVET 3007



EVET 3002

# Sizes

	Size (mm)	Thickness	Finish	Colour Availability
1	Dryback 185 x 1219.2	2	Matt	All colours
2	Rigid Acoustic Click 177.8 x 1219.2	4.5	Matt	All colours

Swatch colours may vary from original. Samples should be requested.

## Specification

- Format:** Plank
- Treatment:** PUR Ecoprotec™
- Texture:** Embossed
- Edge Detail:** 4-way micro-bevel
- Sustainability:** 100% phthalate-free. Low VOC. 100% recyclable
- Durability:** Class 23 Domestic  
Class 31 Commercial
- Application:** Internal use only. Suitable with underfloor heating
- Installation:** Click I4F (Rigid Acoustic Click)  
Recommended for bonded installation (Dryback)  
Recommended for floated installation (Rigid Acoustic Click)

# Eternal 30

## Technical Data

### PERFORMANCE & DURABILITY

Technical Characteristics	Industry Standard	Performance
Product Standard	EN ISO 10582	Heterogeneous resilient floor covering
Total Thickness	EN ISO 24346	2.0mm (Dryback) 4.5mm (Rigid Acoustic)
Wear Layer Thickness	EN ISO 24340	0.30mm
Classification	EN ISO 10874	Domestic: 23 Commercial: 31
Total Weight	EN ISO 23997	3.605g/m <sup>2</sup> (Dryback) 6.450g/m <sup>2</sup> (Rigid Acoustic)
Abrasion Group	EN 660-2	Group T: ≤ 2.00mm <sup>3</sup>
Packing	EN ISO 24342	21 planks/box = 4.74m <sup>2</sup> (Dryback) 60 boxes/pallet = 284.4m <sup>2</sup> (Dryback) 12 planks/box = 2.60m <sup>2</sup> (Rigid Acoustic) 40 boxes/pallet = 104.05m <sup>2</sup> (Rigid Acoustic)
Surface Treatment		PUR Ecoprotec™
Locking System		N/A (Dryback) Click I4F (Rigid Acoustic)
TVOC After 28 Days Indoor Air Quality	ISO 16000-9	≤ 100µg/m <sup>3</sup> (AgBB test)
VOC Emission Class	ISO 16000-9	A+ (French Regulation)
Floorscore VOC Test Indoor Air Quality	ISO 16000-9	Passed
Plasticizer		Phthalate-free
Formaldehyde Group	EN 717-1	E1
Recyclability		100%

### PERFORMANCE & DURABILITY

Technical Characteristics	Industry Standard	Performance
Dimensional Stability	EN ISO 23999	≤ 0.10% (Dryback) ≤ 0.06% (Rigid Acoustic)
Castor Chair	ISO 4918	No damage
Furniture Leg	EN ISO 16581	No damage
Squareness & Straightness	EN ISO 24342	≤ 0.25mm
Residual Indentation	EN ISO 24343-1	≤ 0.10mm
Impact Sound Reduction	EN ISO 717-2	ΔLw = 6dB (Dryback) ΔLw = 21dB (Rigid Acoustic)
Light Fastness	EN ISO 105-B02	≥ 6
Slip Resistance	DIN 51130 EN 13893	R10 DS
Resistance To Chemicals	EN ISO 26987	Not affected (0)
Thermal Resistance	EN ISO 10456	0.02m <sup>2</sup> K/W (Dryback) 0.04m <sup>2</sup> K/W (Rigid Acoustic)
Curl After Exposure To Heat	EN ISO 23999	≤ 2mm
Fire Resistance	EN 13501-1	Bfl-s1
Electrical Properties	EN 1815	≤ 2kV
Resistance Against Staining	EN 26987	Passed
Underfloor Heating Suitability	EN 12524	Compatible (max. 27°C)
Residential Warranty		25 years
Commercial Warranty		5 years

Compatible with underfloor heating systems subject to M50 installation advice available on request.

Test results are based upon current test data provided by the manufacturer and are provided in good faith. Domus Group Ltd. cannot be held responsible for any variation in the test data due to changes in manufacture or material characteristics. Please refer to Domus Group Ltd. Terms & Conditions of Sale, January 2024.



**DOMUS**

service@domusgroup.com | t: 020 8481 9567 | domusgroup.com