Kendo

Porcelain Stone

Wall & Floor: DLKN 02 Soft Textured

3 Colours / **3** Finishes / **6** Sizes / **3** Mosaics

Kendo is inspired by the protected stone of the Deutch Jura Mountains, a stone from marine deposits with numerous markings on its surface. This porcelain tile range depicts dark-coloured organic-shaped markings with an extraordinary richness of intensities.

Floor: DLKN 01 Soft Textured



DLKN 04

DLKN 01

DLKN 02

Sizes



	Size (mm)	Thickness	Finish	Colour Availability
1	1198 x 1198 (R)	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
2	1198 x 598 (R)	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
3	898 x 898 (R)	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
4	898 x 448 (R)	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
5	598 x 598 (R)	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
6	598 x 298 (R)	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours

(R) Rectified size – squared edge with bevel. Mosaics and special pieces shown on next page.
Swatch colours may vary from original. Samples should be requested.

V2 – Moderate
Shade Variation

Mosaics & Special Pieces

Mosaic 25 x 25mm



DLKN 04



DLKN 01



DLKN 02

Mosaic 48 x 48mm



DLKN 04



DLKN 01



DLKN 02

Muretto Mosaic

DLKN 04

DLKN 01

DLKN 02



	Size (mm)	Thickness	Finish	Colour Availability
1	Mosaic 25 x 25 on 298 x 298 sheet	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
2	Mosaic 48 x 48 on 298 x 298 sheet	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
3	Muretto Mosaic on 298 x 298 sheet	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
	Skirting 1198 x 48	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
	Skirting 898 x 48	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours
	Skirting 598 x 48	9	Soft Textured Honed Bush Hammered Anti-Slip	All colours All colours All colours

Swatch colours may vary from original. Samples should be requested.

V2 – Moderate
Shade Variation

DOMUS

service@domusgroup.com | t: 020 8481 9500 | domusgroup.com

Kendo

Technical Data

Product Type: Glazed Porcelain (BS EN 14411 – Group BIa)

Use: Floors & Walls

Product Code: DLKN

DIMENSION & SURFACE QUALITY

Technical Characteristics	Industry Standards	Requirement (for nominal size *N*)		Actual Value
		70mm ≤N<150mm	*N* ≥ 150mm	
Length & width	BS EN ISO 10545-2	± 0.9mm	± 0.60% (max. ± 2.0mm)	Conforms
Thickness	BS EN ISO 10545-2	± 0.5mm	± 5% (max. ± 0.5mm)	Conforms
Edge straightness	BS EN ISO 10545-2	± 0.75mm	± 0.50% (max. ± 1.5mm)	Conforms
Orthogonality (squareness)	BS EN ISO 10545-2	± 0.75mm	± 0.50% (max. ± 2.0mm)	Conforms
Planarity (flatness)	BS EN ISO 10545-2	± 0.75mm	± 0.50% (max. ± 2.0mm)	Conforms
Appearance	BS EN ISO 10545-2	> 95%		Conforms

SLIP RESISTANCE

Technical Characteristics	Industry Standards	Requirement	Finish
Areas with footwear	BS EN ISO 10545-17 (DIN 51130)	R10 from 10° to 19° R11 from 19° to 27°	Soft Textured Bush Hammered Anti-Slip
Areas with bare feet	DIN 51097	B over 18° to 24° C over 24°	Soft Textured Bush Hammered Anti-Slip
Slip resistance (Pendulum) Coefficient of friction	BS 16165	Test results upon request	

All test results are based upon current test data provided by the manufacturer and are provided in good faith. Domus Group cannot be held responsible for any variation in the test data due to changes in manufacture or material characteristics. Errors & omissions excepted. Please refer to Domus Group Terms & Conditions of Sale.

PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Water absorption	BS EN ISO 10545-3	≤ 0.5%	< 0.5%
Modulus of rupture (bending strength)	BS EN ISO 10545-4	≥ 35 N/mm²	> 52 N/mm²
Breaking strength	BS EN ISO 10545-4	≥ 1300 N	> 2,500 N
Resistance to surface abrasion (glazed tiles)	BS EN ISO 10545-7	PEI *see classifications below	3
Thermal shock resistance	BS EN ISO 10545-9	No visible defects	Conforms
Crazing resistance	BS EN ISO 10545-11	No visible signs	Conforms
Frost resistance	BS EN ISO 10545-12	No surface alteration	Conforms
Chemical resistance: Low concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	GLA
High concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	GHA
Domestic chemicals & additives for swimming pools	BS EN ISO 10545-13	UB/GB min.	GA
Stain resistance	BS EN ISO 10545-14	Min. Class 3 – glazed Declared value - unglazed	Class 5
Reaction to fire	Based on the decision 96/603/EC and its changes	$A1_{FL}$/A1	$A1_{FL}$/A1
Recycled content			30%

*PEI classifications
PEI 1 – Very light traffic
PEI 2 - Light traffic
PEI 3 - Light to moderate traffic
PEI 4 - Moderate to heavy traffic
PEI 5 - Heavy to extra heavy traffic

DOMUS

service@domusgroup.com | t: 020 8481 9500 | domusgroup.com