

# Stick

*Porcelain Minimal*



Wall: DTCK 18 Mosaic Glossy

## 27 Colours / 2 Finishes / 1 Mosaic

Stick is a stunning porcelain range of kitkat mosaics available in 27 bold colours and two finishes. Versatile and adaptable, Stick can be installed both vertically and horizontally, making it perfect for walls and floors. Customise your space by choosing grout colours that blend seamlessly or create a striking contrast.




Wall: DTCK 02 Mosaic Matt




Wall: DTCK 12 Mosaic Matt




Wall: DTCK 27 Mosaic Glossy




DTCK 01 Mosaic




DTCK 02 Mosaic




DTCK 03 Mosaic




DTCK 04 Mosaic




DTCK 07 Mosaic




DTCK 08 Mosaic




DTCK 05 Mosaic




DTCK 06 Mosaic




DTCK 09 Mosaic




DTCK 10 Mosaic




DTCK 11 Mosaic




DTCK 15 Mosaic



DTCK 14 Mosaic



DTCK 12 Mosaic



DTCK 13 Mosaic



DTCK 16 Mosaic



DTCK 21 Mosaic



DTCK 22 Mosaic



DTCK 23 Mosaic



DTCK 17 Mosaic




DTCK 18 Mosaic



DTCK 19 Mosaic



DTCK 27 Mosaic



DTCK 24 Mosaic



DTCK 25 Mosaic



DTCK 26 Mosaic



DTCK 20 Mosaic






Wall: DTCK 20 Mosaic Glossy

# Mosaics

1


	Size (mm)	Thickness	Finish	Colour Availability
1	Mosaic 145 x 20 (N) on 300 x 290 sheet	5.5	Matt Glossy	DTCK 01-15 DTCK 16-27

(N) Nominal size – pressed edge. Swatch colours may vary from original. Samples should be requested.



# Stick (Matt)

Technical Data

Product Type: Unglazed Porcelain (BS EN 14411 – Group Bla)

Use: Floors & Walls

Product Code: DTCK 01-15 (Matt)

SLIP RESISTANCE

Technical Characteristics	Industry Standards	Requirement	Finish
Areas with footwear	DIN 51130	R10 from 10° to 19°	Matt
Slip resistance (Pendulum) Coefficient of friction	BS EN 16165 (Annex C)	Test results upon request	

PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Water absorption	BS EN ISO 10545-3	≤ 0.5%	Conforms
Resistance to deep abrasion (unglazed tiles)	BS EN ISO 10545-6	≤ 175 mm³	Conforms
Linear thermal expansion coefficient	BS EN ISO 10545-8	Declared value	< 9*10-6/°C (Typical Value)
Thermal shock resistance	BS EN ISO 10545-9	No visible defects	Resistant
Frost resistance	BS EN ISO 10545-12	No surface alteration	Resistant
Chemical resistance: Low concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	ULA – ULB
High concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	UHA – UHB
Domestic chemicals & additives for swimming pools	BS EN ISO 10545-13	UB/GB min.	UA
Stain resistance	BS EN ISO 10545-14	Declared value - unglazed	Class 5
Reaction to fire	Based on the decision 96/603/EC and its changes	A1FL/A1	A1FL/A1



All test results are based upon current test data provided by the manufacturer and are provided in good faith. Domus Group cannot be held responsible for any variation in the test data due to changes in manufacture or material characteristics. Errors & omissions excepted. Please refer to Domus Group Terms & Conditions of Sale.  
April 2025

# Stick (Glossy)

Technical Data

Product Type: Glazed Porcelain (BS EN 14411 – Group Bla)

Use: Walls

Product Code: DTCK 16-27 (Glossy)

PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Water absorption	BS EN ISO 10545-3	≤ 0.5%	Conforms
Breaking strength	BS EN ISO 10545-4	< 7.5mm ≥ 700 N	Conforms
Resistance to surface abrasion (glazed tiles)	BS EN ISO 10545-7	PEI *see classifications below	Class 2-3
Linear thermal expansion coefficient	BS EN ISO 10545-8	Declared value	< 9*10-6/°C (Typical Value)
Thermal shock resistance	BS EN ISO 10545-9	No visible defects	Resistant
Crazing resistance	BS EN ISO 10545-11	No visible signs	Resistant
Frost resistance	BS EN ISO 10545-12	No surface alteration	Resistant

PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Chemical resistance: Low concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	GLA - GLB
High concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	GHA - GHB
Domestic chemicals & additives for swimming pools	BS EN ISO 10545-13	UB/GB min.	GA
Stain resistance	BS EN ISO 10545-14	Min. Class 3 – glazed	Class 5
Reaction to fire	Based on the decision 96/603/EC and its changes	A1 <sub>FL</sub> /A1	A1 <sub>FL</sub> /A1

**\*PEI classifications**  
PEI 1 - Very light traffic  
PEI 2 - Light traffic  
PEI 3 - Light to moderate traffic  
PEI 4 - Moderate to heavy traffic  
PEI 5 - Heavy to extra heavy traffic



DOMUS

service@domusgroup.com | t: 020 8481 9500 | domusgroup.com