Robur Parquet

Engineered Wood



5 Colours / 1 Finish / 2 Sizes / 2 Formats

PEFC-certified 10mm-thick European oak engineered in 70mm and 120mm-wide strip/ herringbone formats, forested and produced to exacting and responsible standards. Refer to Robur 180, Robur Fundamental 180 and Robur 240 for plank formats.





Floor: WDRO 004 Herringbone Extra Matt UV Lacquer



Floor: WDRO 002 Strip Extra Matt UV Lacquer

Herringbone

Strip



Smoked

WDRO 006












Product Data

Engineered Wood

2 Parquet Formats / 2 Sizes



Herringbone 70 x 490 x 10mm 120 x 1000 x 10mm Strip 70 x 490 x 10mm 120 x 1000 x 10mm

Material: European Oak (Quercus robur)

Grade: Select

Finish: Extra Matt Lacquer, UV fixed

Brushing: Brushed

obur) Certification: PEFC

Treatment: Tinted (WDRO 001, 002 & 004)

Natural (WDRO 005)

Smoked (WDRO 006)

Construction: 10mm (6.5mm engineered spruce base and 3.5mm oak surface layer)

Square-edged (no bevel)
Tongue and groove joints

Application: Internal use only. Suitable with underfloor heating

Installation: Recommended to be fully bonded

Technical Data

Engineered Wood

Cleaning & Maintenance Specification: ETC&M 01

PERFORMANCE & DURABILITY

Technical Characteristics	Industry Standard	Performance
Reaction to Fire	UNI EN 14342 EN 13501-1	Cfl-S1
Formaldehyde Emission	UNI EN 14342 EN 717-1	E1 (≤ 0.05ppm)
VOC Emissions	AgBB-Scheme Blue Angel	≤ 300ppm
Bond Strength	DIN EN 204	≥ D3
Thermal Resistance	UNI EN 14342	0.076m²k/W

NB: Compatible with underfloor heating systems - subject to K21 installation advice available on request.

All test results are based upon current test data provided by the manufacturer and are provided in good faith. Domus Group Limited cannot be held responsible for any variation in the test data due to changes in manufacture or material characteristics. Errors & omissions excepted. Please refer to Domus Group Limited Terms & Conditions of Sale, 27 October 2023 3:05 pm







