Hexography

Glass

Floor: DOHX 17 Mosaic Glass

13 Colours / **3*** Finishes / **1** Mosaic

Hexography is a hexagon-shaped glass mosaic range available in a wide range of colours. Caters for both classic and contemporary interior styles. Mixed finish options embellish walls and floors with colour, texture and pattern.

Floor: DOHX 37 Mosaic Mix (Glass, Natural. Matt Anti-Slip & Honed)

Sizes

Natural Finish

DOHX 01

DOHX 18



DOHX 11

Glass Finish

DOHX 15

DOHX 21

DOHX 17



DOHX 23

Mix Finish (Glass, Natural, Matt Anti-Slip & Honed)

DOHX 52

DOHX 37

DOHX 36

DOHX 39

DOHX 40

DOHX 44

1



	Size (mm)	Thickness	Finish	Colour Availability
1	Mosaic 31.75 x 31.75 on 301 x 290 sheet	4.4	Natural	DOHX 01, 11 & 18
			Glass	DOHX 15, 17, 21 & 23
			Mix[1]	DOHX 36, 37, 39, 40, 44 & 52

Swatch colours may vary from original. Samples should be requested. Mix[1] is a mix of Glass, Natural, Matt Anti-Slip & Honed finishes.

V2 – Moderate Shade Variation

DOMUS

service@domusgroup.com | t: 020 8481 9500 | domusgroup.com

Hexography

Technical Data

Product Type: Glass Mosaic
Use: Walls & Light Duty Barefoot Floors*
Product Code: DOHX

* Except DOHX 12, 21, 23, 26, 30 & 32 which are suitable for walls only

SLIP RESISTANCE

Technical Characteristics	Industry Standards	Requirement	Finish
Areas with footwear	BS EN ISO 10545-17 (DIN 51130)	R9 from 3° to 10° R11 from 19° to 27°	DOHX 01, 05, 08, 11, 15 & 17 Natural and DOHX 18, 34, 36, 39, 40, 44 & 52 Mix[2]
Areas with bare feet	DIN 51097	A over 12° to 18° C over 24°	DOHX 01, 05, 08, 11, 15 & 17 Natural and DOHX 18, 34, 36, 39, 40, 44, & 52 Mix[2]
Slip resistance Coefficient of friction	BS 7976-2 BS EN 16165	Test results upon request	

PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Water absorption	BS EN ISO 10545-3	–	0%
Thermal shock resistance	BS EN ISO 10545-9	–	Resistant
Crazing resistance	BS EN ISO 10545-11	–	Resistant
Frost resistance	BS EN ISO 10545-12	–	Resistant
Chemical resistance: Low concentrations of acids & alkalis	BS EN ISO 10545-13	–	GLA
High concentrations of acids & alkalis	BS EN ISO 10545-13	–	GHA
Domestic chemicals & additives for swimming pools	BS EN ISO 10545-13		GA
Stain resistance	BS EN ISO 10545-14	–	Class 5
Recycled content			98%

All test results are based upon current test data provided by the manufacturer and are provided in good faith. Domus Group cannot be held responsible for any variation in the test data due to changes in manufacture or material characteristics. Errors & omissions excepted. Please refer to Domus Group Terms & Conditions of Sale.
April 2026

RECYCLED CONTENT

DOMUS
service@domusgroup.com | t: 020 8481 9500 | domusgroup.com