

# Truth 1.0 Slab

*Fabricated Slabs / Porcelain Marble*



1 Colour / 1 Finish / 1 Size

Truth 1.0 Slab comprises 12mm-thick fabricated porcelain slabs that stunningly replicate exquisite French marble. This range features a distinctive interplay of soft white veins against rich tones, offering a sophisticated and luxurious aesthetic with the inherent durability of porcelain.

# Sizes

---



DFST 48



	Size (mm)	Thickness	Finish	Colour Availability
1	3200 x 1600	12	Silk	DFST 48

Swatch colours may vary from original. Samples should be requested.

# Truth 1.0 Slab

Technical Data

**Product Type:** Unglazed Porcelain with Glass Fibre Mat Backing

**Use:** Fabrication

**Product Code:** DFST

## DIMENSION & SURFACE QUALITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Thickness	BS EN ISO 10545-2	± 5% (max. ± 0.5mm)	Conforms
Planarity (flatness)	BS EN ISO 10545-2	± 0.50% (max. ± 2.0mm)	Conforms
Appearance	BS EN ISO 10545-2	> 95%	Conforms

## PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Water absorption	BS EN ISO 10545-3	≤ 0.5%	0.08% (Average value)
Modulus of rupture (bending strength)	BS EN ISO 10545-4	≥ 35 N/mm <sup>2</sup>	53 N/mm <sup>2</sup> (Average value)
Breaking strength	BS EN ISO 10545-4	≥ 7.5mm ≥ 1300 N	5000 N (Average value)

## PRODUCT QUALITY & DURABILITY

Technical Characteristics	Industry Standards	Requirement	Actual Value
Impact Resistance	BS EN ISO 14617-9	-	3.03 J (Average value)
Resistance to deep abrasion (unglazed tiles)	BS EN ISO 10545-6	≤ 175 mm <sup>3</sup>	140 mm <sup>3</sup> (Average value)
Thermal shock resistance	BS EN ISO 10545-9	No visible defects	Resistant
Moisture Expansion	BS EN ISO 10545-10	Declared value	0.1 mm/m (Average value)
Frost resistance	BS EN ISO 10545-12	No surface alteration	Resistant
Chemical resistance: Low concentrations of acids & alkalis	BS EN ISO 10545-13	No visible defects	ULA – Matt ULB – Glossy
Domestic chemicals & additives for swimming pools	BS EN ISO 10545-13	UB/GB min.	UA
Stain resistance	BS EN ISO 10545-14	Declared value – unglazed	Class 3-4 – Glossy Class 5 – Matt
Lead Release & Cadmium Release	BS EN ISO 10545-15 BS EN ISO 10545-15	Declared value Declared value	Absent Absent
Reaction to fire	BS EN 13501-1	-	Bfl-s1,d0
Recycled content			5.8%

All test results are based upon current test data provided by the manufacturer and are provided in good faith. Domus Group cannot be held responsible for any variation in the test data due to changes in manufacture or material characteristics. Errors & omissions excepted. Please refer to Domus Group Terms & Conditions of Sale.

**DOMUS**

fabrication@domusgroup.com | t: 020 8481 9500 | domusgroup.com